

Home > Industrial Engines > Tier 3 Stage Iii A
> 6068HF485 6.8L Industrial Diesel Engine



6068HF485

6.8L Industrial Diesel Engine

- 6.8L PowerTech™ Plus
- 134 - 205 kW (180 - 275 hp)

Contact a Distributor

Tier 3 Brochure >

Tier 3 Selection Guide >

Power Connect >

 **Find a Dealer**

 **Sign In**



Search



— 4-valve cylinder head

- The 4-valve cylinder head provides excellent airflow resulting in greater low-speed torque and better transient response.

— High-pressure common-rail (HPCR) and engine control unit (ECU)

- The HPCR fuel system provides variable common-rail pressure, multiple injections, and higher injection pressures, up to 1600 bar (23,000 psi). It also controls fuel injection timing and provides precise control for the start, duration, and end of the injection

— Cooled exhaust gas recirculation (EGR)

- EGR cools and mixes measured amounts of cooled exhaust gas with incoming fresh air to lower peak combustion temperatures, thereby reducing NOx

— Variable geometry turbocharger (VGT)

- Varies exhaust pressure based on load and speed to insure proper EGR flow; greater low-speed torque, quicker transient response, higher peak torque, and best-in-class fuel economy.

— Air-to-air aftercooled

- This is the most efficient method of cooling intake air to help reduce engine emissions while maintaining low-speed torque, transient response time, and peak torque. It enables an engine to meet emissions regulations with better fuel economy and the lowest installed costs

— Compact size

- Horsepower/displacement ratio is best-in-class
- Lower installed cost
- Mounting points are the same as Tier 2/Stage II engine models

— Engine performance

- Greater levels of low speed torque
- Higher levels of power bulge

— John Deere electronic engine controls

- Electronic engine controls monitor critical engine functions, providing warning and/or shutdown to prevent costly engine repairs and eliminate the need for add-on governing components all lowering total installed costs. Snapshot diagnostic data that can be retrieved using commonly available diagnostic service tools
- Controls utilize new common wiring interface connector for vehicles or available OEM instrumentation packages; new solid conduit and "T" connectors to reduce wiring stress and provide greater durability and improved appearance
- Factory-installed, engine mounted ECU or remote-mounted ECU comes with wiring harness and associated components. Industry-standard SAE J1939 interface communicates with other vehicle systems, eliminating redundant sensors and reducing vehicle installed cost

— Additional features

- Glow plugs
- Gear-driven auxiliary drives
- 500-hour oil change
- Self-adjusting poly-vee fan drive
- R.H. and L.H. engine-mounted fuel filters

Show Less

Specifications

Emissions Certifications

CARB



Find a Dealer



Sign In



Search



EU Stage III A

General engine data

Model	6068HF485
Number of cylinders	6
Displacement-- L (cu in)	6.8 (415)
Bore and Stroke-- mm (in)	106 x 127 (4.17 x 5.00)
Compression Ratio	17.0 : 1
Engine Type	In-line, 4-Cycle
Aspiration	Turbocharged and air-to-air aftercooled
Length - mm (in)	1161 (45.7)
Width-- mm (in)	616 (24.3)
Height-- mm (in)	1128 (44.4)
Weight, dry - kg (lb)	678 (1495)

Show More

Drivetrain Components

- Pump Drives
- Transmissions
- Axles
- Planetary Gear Drives

Accessories

- Engine Accessories Brochure

Parts

- Engine Parts