



## Type

- 4 Stroke
- Air Cooled
- V Twin
- Overhead valve
- Vertical Shaft

## Features

- Single stage canister air filter
- High performance lubrication system
- Cast iron cylinder liners
- Internally vented carburetor with fuel shut-off solenoid
- Automatic compression release
- Metal engine cover
- 90 degree V-twin
- Electronic spark ignition
- Spherical combustion chamber
- Clean-out ports
- Heavy duty shift type starter
- Overhead V-valves
- Rotating grass screen

## Options

- Shaft variations
- Various speed control system
- 13 or 20 Amp charge coil
- Various oil drains

## Technical Specifications

Engine Type	Air-cooled, 4-stroke, V-twin, Vertical shaft, OHV
Max. power	12.7 kW (17.0 hp) / 3600 rpm
Oil capacity (litres)	2.0 litres
Number of cylinders	2
Displacement	603cm <sup>3</sup>
Dimensions (L x W x H) (mm)	468 x 429 x 544
Bore x stroke	73 x 72 mm
Fuel tank capacity (litres)	
Max. torque	40.4 Nm (29.8 ft.lbs) / 2200 rpm
Dry weight	40.7 Kg

## Performance curves

The power rating of this engine is the Net power rating tested on a production engine and measured in accordance with SAE J1349. Actual power output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.



