



Туре

- 4 Stroke
- Air Cooled
- V Twin
- Overhead valve
- Vertical Shaft

Features

- High performance lubrication system
- Cast iron cylinder liners
- Automatic compression release
- Dual stage canister air filter
- Metal engine cover
- 90 degree V-twin
- Electronic spark ignition

• Twin barrel, internally vented carburetor with fuel shut-off solenoid

- Spherical combustion chamber
- Clean-out ports
- Heavy duty shift type starter
- Overhead V-valves
- Rotating grass screen

Options

- Shaft variations
- Various speed control system
- 13 or 20 Amp charge coil
- Various oil drains

Technical Specifications

 Engine Type 	Air-cooled, 4-stroke, V-twin, Vertical shaft, OHV
 Max. power 	15.4 kW (20.6 hp) / 3600 rpm
 Oil capacity (litres) 	2.0 litres
 Number of cylinders 	2
 Displacement 	726cm ³
Dimensions (L x W x H) (mm)	479 x 462 x 565
 Bore x stroke 	78 x 76 mm
 Fuel tank capacity (litres) 	
 Max. torque 	53.7 Nm (39.6 ft.lbs) / 2000 rpm
 Dry weight 	46.0 Kg

Performance curves

The power rating of this engine is the Net power rating tested on a production engine and measured in accordance with SAE J1349.Actual power output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.





