

NEW JD14 & JD18

Marine Engines

298 - 599 kW



JOHN DEERE

A NEW ERA IN POWER



Announcing the all-new John Deere JD14 and JD18 marine engines. They're built to take your marine propulsion, auxiliary, and generator applications to the next level.

POWERFUL PERFORMANCE.

JD14 engines have **higher duty cycles** and more power than John Deere 13.5L models.

JD18 engines are built for heavy-duty commercial marine applications up to 599 kW (803 hp).

High-pressure common-rail (HPCR) provides flexible injection timing and excellent efficiency.

MACHINE AVAILABILITY.

John Deere Connected Support™ remote monitoring and diagnostics comes standard. It provides protection and efficiency with no subscription fees or ongoing expenses.

John Deere JD14 and JD18 engines provide **excellent fuel economy**.

The JD18 has independent cooling for jacket water and aftercooling systems.

LOW MAINTENANCE.

Longer oil change service intervals up to 500 hours when you use John Deere Plus-50™ II engine oil.

Rigid bronze impeller on seawater pump with up to 10,000-hour life before needing maintenance.

Hydraulic automatic valve lash adjustment improves durability and eliminates valve lash maintenance.

EASY INTEGRATION.

The JD14 marine engine features a reduced package size compared to the John Deere 13.5L.

The on-board ECU and compact service center box provides easy wiring and integration.

Standard front side service for oil and filter maintenance.

	JD14P	JD14X	JD18P
General data			
Type	6-cylinder, In-line, 4-valve, 4-stroke diesel		
Displacement	13.6L	13.6L	18.0L
Fuel system	Electronic high-pressure common-rail (HPCR)		
Gear train	Rear gear train – 2 PTOs		
Cooling	Keel cooled or Heat exchanger	Heat exchanger	Keel cooled or Heat exchanger
Aftercooler	Air-to-coolant	Air-to-seawater	Air-to-coolant (separate circuit)
Turbocharger	Single-stage water cooled (fixed)		
Performance			
Rated power	298 – 448 kW (400 – 600 hp) @ 1800 – 2100 rpm	523 – 599 kW (700 – 803 hp) @ 2100 – 2200 rpm	410 – 599 kW (550 – 803 hp) @ 1800 – 2100 rpm
Service interval	Up to 500 hours with John Deere Plus-50™ II engine oil		
Emissions technology			
Certification	IMO Tier 2 / EPA Tier 3 / EU RCD 2		
Classifications	ABS, DNV-GL, LR		
EGR	No		
Aftertreatment	No		
Specifications			
Dimensions (L x W x H)	1750 x 1128 x 1192 mm (69 x 44 x 47 in)	1750 x 1095 x 1192 mm (69 x 43 x 47 in)	2063 x 1321 x 1298 mm (81 x 52 x 51 in)
Weight	~1436 kg (3166 lb)	~1489 kg (3283 lb)	~2100 kg (4630 lb)

Preliminary information. Specifications are subject to change. Dimensions may vary based on options selected.




Divisione di RAMA S.p.A.

Via Agnoletti, 8 - 42124 Reggio Emilia

+39 0522 930711

marine@rama.it

ramamarine.it